



# EXCELLO BOILER COMPOUND

---

## FOR TREATMENT OF WATER IN HEATING PLANTS

**DEFIANCE EXCELLO BOILER COMPOUND** is designed for use as an internal treatment for the prevention of scale and corrosion in steam boilers.

### FEATURES

- ◆ 100% Soluble in Water
- ◆ Helps prevent foaming, priming and carryover
- ◆ Peptizing action aids in preventing sludge problems
- ◆ Helps prevent caustic embrittlement by controlling boiler water alkalinities
- ◆ Causes precipitate to form for easy clean-up

### Directions For Use:

1. Flush boiler thoroughly to remove loose scale and sludge.
2. Fill boiler with fresh water to operating level. Add enough Excello Boiler Compound to reach a ph of 11 or above.
3. Operate boiler. Check ph of Boiler– blow down water once a day. Add enough Excello Boiler Compound to maintain boiler water at a ph of 11 or add 1/2 gallon of Excello Boiler Compound to each 200 gallons of water.
4. Blow down boiler once each day for one minute to maintain boiler water solids at proper concentration.

**Packaged in 55 and 30 gal. drums 5 gal. pails and 6x1 gallon cases**

Since 1924

**Omaha Compound Company**

2001 Nicholas Street ♦ Omaha, Nebraska 68102

Tel: 402-346-7117 ♦ Fax: 402-346-2040

---